

58, Paige Close, The Meadows, Watlington King's Lynn, Norfolk PE33 0TQ

Tel 01553 811977 Fax 01553 811004 Mobile 07768506297

E-mail: sales@manualhandlingsolutions.co.uk

www.manualhandlingsolutions.com

## MezzLift Specification - Central Presentations 200kg

**Maximum Working Load** 

Travel

**Platform Size Platform Guarding** 

Lift Speed

**Number of stops** 

**Power Supply Required** 

**Controls Drive Type** 

**Loading Configuration** 

Pit

**External Shaft Size Shaft Enclosure** 

**Documentation** 

**Door Type** 

Self supporting 1" x 1" mesh shaft

1750mm x 850mm to suit application

2 (ground and mezzanine)

Chain drive, hydraulic motor

None - loading via 50mm ramp

On/off same side

1340mm x 2000mm

900mm high frames to suit loading direction

2000mm Clear height single gate, mesh filled. Lift gates are protected

by electrical interlocks to prevent access to the shaft unless the

240v, 20amp, 1 phase terminated in a double pole isolator switch

Push to run controls adjacent to the gates at both levels

platform is docked at the appropriate level CE Mark with Declaration of Conformity

Operation and Maintenance Manual issue on completion LOLER Report of Thorough Examination and Test issued on

commission

200kg

2740mm

0.3 m/s

**Training** Operator training carried out on completion

